

Material Product Datasheet

L3353500 FanTastock Gloss Piggyback Polyester Label

FACE STOCK

Description Gloss Polyester

Caliper Target (mils) 2

MD Tensile Target (lb/in)
CD Tensile Target (lb/in)

ADHESIVE

Description Acrylic Permanent

Caliper Target (mils) 0.9

Peel adhesive Target on Stainless Steel (lb/in)

LINER

Description 1.5 mil polyester

Caliper Target (mils) 1.4

TOTAL CALIPER TARGET (mils) 8.3

ENVIRONMENT

Storage Humidity (%)

Storage Temperature (°F) 40 to 80

to 75

35

Shelf Life (months) 12 Minimum Application Temp (°F) 50

Service Temperature (°F) -40 to 302

Sample Part #

RIBBON COMPATIBILITY

TMX1000 Series Wax

TMX2000 Series Mid-Range

✓ TMX3000 Series Resin

COMPLIANCE

UL

FDA.21 CFR 175.105

CSA

cUL

BPA-Free

FSC-Certified

RECOMMENDED FOR SELF-STRIP

NO

MAXIMUM OUTDOOR LIFE

< 6 months

< 12 months

< 18 months

✓ 5+ Years

TYPICAL APPLICATIONS

Shipping / Receiving

Work in Process (WIP)

Rack/Shelf/Bin

✓ Durable Goods

Lock out / Tag out (LOTO)

✓ Asset / Tool Marking

Special Notes

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.