



Material Product Datasheet

L3501039
Duratran Pro Label

FACE STOCK

Description	Polyethylene
Caliper Target (mils)	4.2
MD Tensile Target (lb/in)	
CD Tensile Target (lb/in)	

ADHESIVE

Description	Acrylic Permanent
Caliper Target (mils)	0.7
Peel adhesive Target on Stainless Steel (lb/in)	

LINER

Description	55# SCK
Caliper Target (mils)	3.2

TOTAL CALIPER TARGET (mils) 8.1

ENVIRONMENT

Storage Temperature (°F)	35	to	75
Storage Humidity (%)	35	to	75
Shelf Life (months)	12		
Minimum Application Temp (°F)	45		
Service Temperature (°F)	-65	to	200

Sample Part # E15158_S
E13275_S

RIBBON COMPATIBILITY

- ✓ TMX1000 Series Wax
- ✓ TMX2000 Series Mid-Range
- TMX3000 Series Resin

COMPLIANCE

- UL
- FDA.21 CFR 175.105
- CSA
- cUL
- BPA-Free
- FSC-Certified

RECOMMENDED FOR SELF-STRIP



MAXIMUM OUTDOOR LIFE

- < 6 months
- ✓ < 12 months
- < 18 months
- 5+ Years

TYPICAL APPLICATIONS

- Shipping / Receiving
- Work in Process (WIP)
- ✓ Rack / Shelf / Bin
- Durable Goods
- Lock out / Tag out (LOTO)
- ✓ Asset / Tool Marking

Special Notes

Industrial bins, Horticultural labeling, Chemical drum labels, Medical devices and specimens, Building products, Automotive components, Farm equipment, Oil and gas industries

Important Notice: Information presented herein is believed to be accurate based on research with no guarantee of accuracy or completeness. Product must be thoroughly tested under end-use conditions to ensure that it meets all intended requirements. Datasheet does not imply any warranty or guarantee. User assumes all risk and liability in connection with end-use of product.

Honeywell Productivity Products - Printer Supplies

Printed on:
3/14/2019

9290 LeSaint Drive
Fairfield, Ohio 45014
800-755-5505 opt 2