

# XD3-40 Series

4-inch Desktop Label Printers



Retail



Warehouse



Healthcare



Logistics

# Durable and Cost-Effective



XD3-40d



XD3-40t



### Basic Functions

- Printing speeds of up to 5ips (127mm/sec)
- Fully compatible with market-leading programming languages
- Simple to set up through a single LED
- Smart switch programming languages without setting the mode



### User-Friendly Design

- Easy paper loading with adjustable paper guide and holder
- Easy set up media sensor
- Optional peeler and external paper supply
- Toolless maintenance of roller and print head
- Suitable for both 1/2-inch and 1-inch core ribbon (74 m and 300 m)



### Connectivity Options

- Standard: USB
- Optional: USB + Serial + Ethernet

# XD3-40 Series

## 4-inch Desktop Label Printers

### Specifications

#### Printer Specifications

**Print Method**

XD3-40d : Direct Thermal  
XD3-40t : Thermal Transfer or Direct Thermal

**Print Speed**

Up to 5 ips (127 mm/sec)

**Print Resolution**

203 dpi

**Print Width**

Up to 104 mm

**Print Length**

Up to 1,000 mm

**Sensor**

Transmissive(Fixed), Reflective(Adjustable),  
Ribbon-End (XD3-40t), Head Open

#### Media Characteristics

**Media Type**

Gap, Black Mark, Notch, Continuous,  
Fan-Fold

**Media Width**

15 ~ 118 mm

**Media Roll Diameter**

Up to 127 mm

**Media Thickness**

0.06 ~ 0.20 mm

**Supply Method**

Easy Paper Loading

**Inner Core**

25.4 ~ 38.1mm

#### Ribbon Characteristics

**Ribbon Type**

Wax, Wax / Resin, Resin, Outside

**Ribbon Width**

33 ~ 110mm

**Ribbon Length**

Up to 300m

**Core Inner Diameter**

25.4 mm, 12.7 mm

#### Physical Characteristics

**Dimensions (WxDxH)**

XD3-40d : 181 x 222 x 168 mm  
(7.13 x 8.74 x 6.62 inch)  
XD3-40t : 210 x 284 x 186 mm  
(8.3 x 11.2 x 7.3 inch)

**Weight**

XD3-40d : 1.7kg (3.75 lbs.)  
XD3-40t : 2.6kg (5.73 lbs.)

**Electrical**

EnergyStar Certified,  
External Power Adaptor 100-240V AC,  
50/60Hz

#### Performance Characteristics

**Memory**

64 MB SDRAM, 128 MB Flash

**Interface**

Standard: USB  
Optional: USB + Serial + Ethernet

**Real Time Clock**

Not Supported

#### Environment Characteristics

**Temperature**

Operating: XD3-40d: 0 ~ 40°C (32 ~ 104°F)  
XD3-40t: 5 ~ 40°C (41 ~ 104°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

#### Software

**Emulation**

SLCSTM, BPL-ZTM (ZPLII), BPL-ETM (EPL)

**Driver / Utility**

Windows Driver (Europlus / Seagull)  
Linux / Mac CUPS Driver  
Virtual COM USB / Ethernet Driver  
Utility Program  
OPOS Driver  
Bartender Ultralite for BIXOLON  
Label Artist-II™

**SDK / Plugin**

Windows SDK, Linux SDK

#### Fonts / Graphics / Symbologies

**Fonts**

Bitmap Fonts (SLCS, BPL-Z, BPL-E) /  
Scalable Fonts (SLCS, BPL-Z) /  
Unicode supported  
(UTF-8, UTF-16LE, UTF-16BE)

**Graphics**

Supporting user-defined fonts, graphics,  
formats and logos

**Barcode Symbologies**

1D: Codabar, Code 11, Code 39, Code 93,  
Code 128, EAN-13, EAN-8,  
Industrial 2-of-5, Interleaved 2-of-5,  
Logmars, MSI, Plessey, Postnet,  
GS1 DataBar (RSS-14), Standard 2-of-5,  
UPC/EAN extensions, UPC-A, UPC-E,  
IMB  
2D: Aztec, Codablock, Code49, Data Matrix,  
MaxiCode, MicroPDF417, PDF417,  
QR Code, TLC39

#### Accessories

**Standard**

Cable-USB

**Options**

Peeler, External Paper Supply

