



- Print speeds up to 8 ips (format & carrier dependent)
- Prints on paper labels and tags
- Best performance for value solution
- Moderate smudge & scratch resistance
- Prints at low print head energy heat settings

TECHNICAL DATA

RIBBON PROPERTY	
Base Material	Polyester Film
Ink Color	Black
Transmission Density	1.95
Back Coating	Yes
Total Thickness	7.1 ± 0.3 µm
PET Thickness	4.4 µm
Optical Density	≥ 1.82 D
Ink Melt Point	154.4°F (68°C)
Recommended Substrates	Art paper, coated and uncoated paper, tag stocks
DURABILITY OF PRINTED IMAGE	
Smudge & Scratch Resistance	Moderate
Storage Condition	40°-90°F (5-35°C), 20-85% RH
Storage Life	1 year after manufacturing
APPLICATION FIELDS	

Inventory, Carton/Shipping, Cross-Docking, Retail Labeling, Work In Process, Signage & Logos, Laboratory, Healthcare, Tags, Click and Collect, Livestock, Conveyor Sorting, Kanban Labeling

Please contact us if your application is not among these.

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

9007035

