



Red Resin Ribbon

This high performance red resin ribbon is designed for use in applications requiring a durable red resin ribbon.

With 8000T GHS Vinyl and 8000T GHS Polyester, this red resin ribbon meets BS 5609 Section 2 and Section 3. This is the marine immersion testing required for IMDG (International Maritime Dangerous Goods).

SUGGESTED APPLICATIONS

- Chemical drum labeling applications



TECHNICAL SPECIFICATIONS

Attribute	Specification
Color	Red
Ink Formulation	Resin
Base Film	Polyester
Base Film Caliper	4.5 microns
Scanning Capabilities	None
Ribbon Length(s) / Inner Core Width(s)	300m (984 ft.) / 25.4mm (1.0")
Stocked Widths (450m length)	110, 154 mm (4.33", 6.06")

Recommended Storage Conditions: 23°F to 104°F (-5°C to 40°C) at 20% to 85% RH

Shelf Life 1 year

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.